



Hot Shot

Heating Oil Treatment

The best heating oil performance additive, HOT SHOT enhances all-around performance and helps protect your heating system against expensive breakdowns.

- Totally Disperses Water
- Improves Combustion
- Cleans Fuel System
- Inhibits Corrosion
- Stabilizes Fuel
- Dissolves Sludge

PART#	SIZE	UNITS/CS	TREATS	DIRECTIONS
H15-16	16 OZ	24	275 GL	Use 1 OZ to every 17 GL of fuel
H15-01	1 GL	6	2,200 GL	Use 1 GL to every 2,200 GL of fuel
H15-05	5 GL	1	11,000 GL	Use 1 GL to every 2,200 GL of fuel
H15-55	55 GL	1	121,000 GL	Use 1 GL to every 2,200 GL of fuel
H15-275	275 GL	1	605,000 GL	Use 1 GL to every 2,200 GL of fuel

An overtreatment of additive is not harmful. For best results, add additive before filling tank.

BIODIESEL-SAFE FORMULA

All E-ZOIL heating oil additives are safe for use with bio-based heating oils.

For maximum heating oil performance, reach for HOT SHOT!



E-ZOIL

Performance. Pour it on.

234 Fillmore Avenue, Tonawanda, New York 14150
855-MY-EZOIL EZOIL.com