

**MATERIAL SAFETY DATA SHEET
STORZALL**

SECTION I – MANUFACTURER’S NAME AND CONTACT INFORMATION

Manufacturer

E-ZOIL Products, Inc.
234 Fillmore Avenue
Tonawanda, NY 14150

Emergency 1-800-633-8253 PERS
Information 716-213-0106
Date prepared July 1, 2011

NFPA Code: Health 2 Fire 2 Reactivity 0

SECTION II – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Components	CAS Number	% by Weight
Light aromatic naphtha	64742-95-6	5-10
1,2,4- trimethylbenzene	95-36-6	5-10
1,3,5- trimethylbenzene	108-67-8	1-5
Xylene	1330-20-7	10-30
Refined heavy paraffinic distillates	64741-88-4	1-5
Petroleum distillates	64742-65-0	1-5
Amine compound	Trade secret	10-30
Ethylbenzene	100-41-4	1-5
Amino alkylphenolic resins	Trade secret	10-30

SECTION III – PHYSICAL & CHEMICAL CHARACTERISTICS

Physical State and Appearance: Liquid	Odor: Aromatic	Color: Yellow
pH	Not available	
Specific Gravity	0.882 – 0.894 @ 16 C (60 F)	
Density	7.35 – 7.45 lbs/gal @ 16 C (60 F)	
Vapor Density	>1 (Air=1)	
Vapor Pressure	4.6 – mmHg @ 21 C (70 F)	
Evaporation rate	Not available	
Viscosity	11-13 cps	
Pour Point	< -48 C (<-55 F)	
Solubility (Water)	Insoluble	
Boiling Point	Not available	

SECTION IV – FIRE & EXPLOSION HAZARD DATA

Flammability of product: Combustible liquid. At elevated temperatures, vapors can form an ignitable or explosive mixture with air. Can form explosive mixtures at temperatures at or above the flash point. Static discharges can cause ignition or explosion when container is not bonded.

OSHA Flammability Class II

Flash Point Closed cup 110° F

Products of Combustion - These products are carbon oxides and nitrogen oxides.

In case of fire, use foam, dry chemicals or CO2 fire extinguishers. Evacuate area and fight fire from a safe distance.

Water spray may be used to keep fire exposed containers cool. Vapors may travel considerable distances and flash back if ignited.

