

SAFETY DATA SHEET DIESEL AID + CETANE

SECTION 1: IDENTIFICATION

Product Name: Diesel Aid + Cetane

Product Code: D25

Product Use: Diesel additive

Manufacturer's Name: E-ZOIL Products, Inc. Address: 234 Fillmore Avenue

Address: Tonawanda, NY 14150 USA

Business Phone: 855-693-9645

Emergency Phone: 800-633-8253 PERS
Date of Preparation: October 1, 2015
Date of Last Revision: June 1, 2020

Regulatory Standard: CFR29 1910.1200 HazCom 2012

SECTION 2: HAZARDS IDENTIFICATION

GHS-US classification Flammable Liquid 4 Acute toxicity 4 (Oral) Skin Irritation 2 Eye Irritation 2A Carcinogenicity 2 Aspiration Toxicity 1

Hazard pictograms (GHS-US):







Signal word (GHS-US): Danger

Hazard statements (GHS-US): Combustible liquid. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways.

Precautionary statements: Keep away from flames/hot surfaces. No smoking. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice or attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/ attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local, regional, national and international regulations.

Other information: None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS Number	%	
Ethylene glycol butyl ether	111-76-2	60 - 80	
2-ethylhexyl nitrate	27247-96-7	10 - 20	
Triethanolamine	102-71-6	1 - 5	
Fatty Acid	Trade Secret	1 - 5	
Benzene, trimethyl-	25551-13-7	1 - 5	
1,3,5-Trimethylbenzene	108-67-8	1 - 5	
Naphthalene	91-20-3	1 - 5	

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: FIRST AID MEASURES

First-aid measures after inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact: In case of contact, immediately flush skin with plenty of water. Remove

contaminated clothing and shoes. Wash clothing before reuse. Call a physician if

irritation develops and persists.

First-aid measures after eye contact: In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get

medical attention.

First-aid measures after ingestion: If swallowed, do NOT induce vomiting. Immediately call a POISON CENTER or

doctor/physician. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed:

Symptoms/injuries after inhalation: May cause respiratory tract irritation.

Symptoms/injuries after skin contact: Causes skin irritation. Symptoms may include redness, edema, drying, defatting

and cracking of the skin.

Symptoms/injuries after eye contact: Causes serious eye irritation. Symptoms may include discomfort or pain, excess

blinking and tear production, with marked redness and swelling of the

conjunctiva.

Symptoms/injuries after ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting. May be

fatal if swallowed and enters airways. This product may be aspirated into the

lungs and cause chemical pneumonitis.

Indication of any immediate medical attention and special treatment needed:

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: FIRE FIGHTING MEASURES

Suitable extinguishing media: Foam. Dry chemical. Carbon dioxide.

Unsuitable extinguishing media: None known.

Fire hazard: Combustible liquid. Products of combustion may include, and are not limited to:

oxides of carbon.

Protection during firefighting: Keep upwind of fire. Wear full firefighting turn-out gear (full Bunker gear) and

respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to

keep fire-exposed containers cool.

SECTION 6: ACCIDENTAL RELEASE MEASURES

General measures: Use personal protection recommended in Section 8. Isolate the hazard area and

deny entry to unnecessary and unprotected personnel. Eliminate sources of

ignition.

For containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place

in a suitable container. Do not flush to sewer or allow to enter waterways. Use

appropriate Personal Protective Equipment (PPE).

Methods for cleaning up: Scoop up material and place in a disposal container. Provide ventilation.

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: HANDLING AND STORAGE

Additional hazards when processed: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling: Keep away from sources of ignition - No smoking. Use only outdoors or in a well-

ventilated area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use personal protective

equipment as required.

Hygiene measures: Launder contaminated clothing before reuse. Wash hands before eating,

drinking, or smoking.

Technical measures: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions: Keep out of the reach of children. Store in original container protected from direct

sunlight in a dry, cool and well-ventilated area. Keep container tightly closed

when not in use.

Storage temperature: 39 – 120°F

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ethylene glycol butyl ether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³

OOLIA DEL (TMA) (mm m)	FO	
OSHA PEL (TVVA) (ppm)	50 ppm	
ACGIH TWA (mg/m³)	5 mg/m³	
Not applicable		
Not applicable		
Not applicable	Not applicable	
I- (25551-13-7)		
ACGIH TWA (ppm)	25 ppm	
Not applicable	Not applicable	
zene (108-67-8)		
Not applicable	Not applicable	
SHA Not applicable		
0-3)		
ACGIH TWA (ppm)	10 ppm	
OSHA PEL (TWA) (mg/m³)	50 mg/m ³	
OSHA PEL (TWA) (ppm)	10 ppm	
	Not applicable Not applicable I- (25551-13-7) ACGIH TWA (ppm) Not applicable Izene (108-67-8) Not applicable Not applicable ACGIH TWA (ppm) OSHA PEL (TWA) (mg/m³)	O2-71-6) ACGIH TWA (mg/m³) Not applicable Not applicable Not applicable I- (25551-13-7) ACGIH TWA (ppm) Not applicable Izene (108-67-8) Not applicable Not applicable Not applicable ACGIH TWA (ppm) OSHA PEL (TWA) (mg/m³) 5 mg/m³ 5 mg/m³ 5 mg/m³

2-Ethylhexyl nitrate (27247-96-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

Appropriate engineering controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor,

etc.) below recommended exposure limits.

Hand protection: Wear chemically resistant protective gloves.

Eye protection: Wear safety glasses with side shields or goggles.

Skin and body protection: Wear suitable protective clothing.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator

selection must be based on known or anticipated exposure levels, the hazards of

the product and the safe working limits of the selected respirator.

Environmental exposure controls: Maintain levels below community environmental protection thresholds.

Other information: Do not eat, smoke or drink where material is handled, processed or stored. Wash

hands carefully before eating or smoking. Handle according to established

industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Appearance: No data available

E-ZOIL Products, Inc. www.EZOIL.com Page 4 of 8

Color: Light yellow

Odor: Mild

Odor threshold:

PH:

No data available

Relative evaporation rate:

No data available

Flammability (solid, gas): Flammable

Explosive limits:

Explosive properties:

Oxidizing properties:

Vapor pressure:

No data available

Relative density: 0.897

Relative vapor density at 20 °C: 4.1 (Air = 1)Solubility: Water > 90% Partition coefficient: n-octanol/water: No data available Log Kow: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity: No data available Viscosity, kinematic: No data available Viscosity, dynamic: No data available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability: Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use.

Conditions to avoid: Heat. Incompatible materials. Sources of ignition.

Incompatible materials: Oxidizers.

Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity: Harmful if swallowed.

Diesel Aid + Cetane	
LD50 oral rat	> 300 but ≤ 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Diesel Aid + Cetane		
LC50 inhalation rat	> 20 mg/l/4h	
Ethylene glycol butyl ether (111-76-2)		
LD50 oral rat	1300 mg/kg	
Triethanolamine (102-71-6)		
LD50 oral rat	4190 mg/kg	

LD50 dermal rabbit	> 20 ml/kg		
Fatty Acid			
LD50 oral rat	25 g/kg		
Benzene, trimethyl- (25551-13-7)	Benzene, trimethyl- (25551-13-7)		
LD50 oral rat	8970 mg/kg		
1,3,5-Trimethylbenzene (108-67-8)			
LC50 inhalation rat	24 g/m³/4h		
Naphthalene (91-20-3)			
LD50 oral rat	490 mg/kg		
LD50 dermal rabbit	> 20 g/kg		
2-Ethylhexyl nitrate (27247-96-7)			
LD50 oral rat	> 2000 mg/kg		
LD50 dermal rabbit	> 4820 mg/kg		
LC50 inhalation rat	> 14 mg/l/4h		

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitization: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Suspected of causing cancer.

Ethylene glycol butyl ether (111-76-2)		
IARC group	3 - Not classifiable	
Triethanolamine (102-71-6)		
IARC group	3 - Not classifiable	
Naphthalene (91-20-3)		
IARC group	2B - Possibly carcinogenic to humans	
	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen	

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation: May cause respiratory tract irritation.

Symptoms/injuries after skin contact: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting. May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis.

SECTION 12: ECOLOGICAL INFORMATION

Ecology - general: May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Diesel Aid + Cetane

Persistence and degradability Not established.

Bioaccumulative potential

Diesel Aid + Cetane

Bioaccumulative potential Not established.

Mobility in soil: No additional information available

Other adverse effects: Effect on the global warming – No known ecological damage caused by this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste disposal recommendations: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

UN number: NA1993

Proper shipping name: Combustible liquid, n.o.s., (Ethylene glycol monobutyl ether)

Transport hazard class(es): Combustible liquid

Packing group: III

This product may be reclassed as a combustible liquid. Refer to 49 CFR Section 173.150.

This product is not regulated for road or rail transportation in the United States if packaged in non-bulk containers equal to or less than 119 Gallons/450 liters.

SECTION 15: REGULATORY INFORMATION

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Federal regulations:

1,3,5-Trimethylbenzene (108-67-8)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Naphthalene (91-20-3)	
Subject to reporting requirements of United States SARA Section 313	

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under
	TSCA.
SARA Section 313 - Emission Reporting	0.1 %

State regulations:

Diesel Aid + Cetane	
State or local regulations	This product contains a chemical known to the State of California to
	cause cancer.

SECTION 16: OTHER INFORMATION

Other information: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.