



D-Gel

Emergency Cold Weather Performance Additive

The best emergency diesel fuel performance additive, D-GEL reliquifies gelled & iced diesel fuel & filters to get you running again.

- Reliquifies Gelled Fuel
- Reliquifies Iced Fuel
- Deices Iced Fuel Filters
- Improves Cold Flow
- Helps Remove Water

PART #	SIZE	UNITS/CS	TREATS	DIRECTIONS
F10-16	16 OZ	24	50 GL	Use 1 OZ to every 15 GL of fuel
F10-01	1 GL	6	400 GL	Use 1 GL to every 1,920 GL of fuel
F10-05	5 GL	1	2,000 GL	Use 1 GL to every 1,920 GL of fuel
F10-55	55 GL	1	22,000 GL	Use 1 GL to every 1,920 GL of fuel
F10-275	275 GL	1	110,000 GL	Use 1 GL to every 1,920 GL of fuel

An overtreatment of additive is not harmful.
For best results, add additive before filling tank.

ULSD Formula

E-ZOIL performance additives are formulated for today's Ultra Low Sulfur Diesel. They meet all emission standards and provide added protection for your valuable diesel-powered equipment. All E-ZOIL diesel fuel additives are safe for use with biodiesel fuel.

For emergency diesel fuel de-gelling , reach for D-GEL!



E-ZOIL

Performance. Pour it on.

855-MY-EZOIL EZOIL.com Made in the USA