

Diesel Aid + Cetane

All-Around Performance Additive

The best all-around diesel fuel performance additive, DIESEL AID + CETANE protects critical fuel system parts while improving power. DIESEL AID + CETANE emulsifies water to prevent fuel system failure, increases cetane & lubricity, improves cold flow & cleans your fuel system.

- Increases Cetane
- Improves Fuel Economy
- Totally Disperses Water
- Improves Cold Flow
- Improves Lubricity
- Inhibits Corrosion

PART #	SIZE	UNITS/CS	TREATS	DIRECTIONS
D25-16	16 OZ	12	240 GL	Use 1 OZ to every 15 GL of fuel
D25-01	1 GL	1	1,920 GL	Use 1 GL to every 1,920 GL of fuel
D25-05	5 GL	1	9,600 GL	Use 1 GL to every 1,920 GL of fuel
D25-55	55 GL	1	105,600 GL	Use 1 GL to every 1,920 GL of fuel
D25-275	275 GL	1	528,000 GL	Use 1 GL to every 1,920 GL of fuel

An overtreatment of additive is not harmful.
For best results, add additive before filling tank.

ULSD Formula

E-ZOIL performance additives are formulated for today's Ultra Low Sulfur Diesel. They meet all emission standards and provide added protection for your valuable diesel-powered equipment. All E-ZOIL diesel fuel additives are safe for use with biodiesel fuel.

For maximum diesel power, reach for DIESEL AID + CETANE!



E-ZOIL

Performance. Pour it on.

855-MY-EZOIL EZOIL.com Made in the USA

