



D-Gel

Emergency Cold Weather Performance Additive

The best emergency diesel fuel flow performance additive, D-Gel reliquifies gelled diesel fuel to get you running again.

- Reliquifies Gelled Fuel
- Reliquifies Iced Fuel
- Deices Iced Fuel Filters
- Improves Cold Flow
- Helps Remove Water

PART#	SIZE	UNITS/CS	TREATS	DIRECTIONS
F10-16	16 OZ	24	50 GL	Use 1 OZ to every 3 GL of fuel
F10-01	1 GL	6	400 GL	Use 1 GL to every 400 GL of fuel
F10-05	5 GL	1	2,000 GL	Use 1 GL to every 400 GL of fuel
F10-55	55 GL	1	22,000 GL	Use 1 GL to every 400 GL of fuel
F10-275	275 GL	1	110,000 GL	Use 1 GL to every 400 GL of fuel

For best results, add additive before filling tank.

ULSD Formula

E-ZOIL performance additives are formulated for today's Ultra Low Sulfur Diesel. They meet all emission standards and provide added protection for your valuable diesel powered equipment.

For emergency diesel fuel de-gelling , reach for D-GEL!



E-ZOIL
Performance. Pour it on.

234 Fillmore Avenue, Tonawanda, New York 14150
855-MY-EZOIL EZOIL.com Made in the USA