



Diesel Fire

Summer Performance Additive

The best warm weather demulsifier diesel fuel additive, Diesel Fire, enhances all-around performance and helps you avoid expensive breakdowns. Diesel Fire demulsifies water, increases cetane up to 6 points, increases lubricity, and cleans fuel systems by removing deposits including those found in high pressure common rail engines.

- Increases Fuel Economy
- Increases Cetane
- Increases Lubricity
- Cleans Fuel Systems
- Reduces Exhaust Emissions
- Separates Water

PART#	SIZE	UNITS/CS	TREATS	DIRECTIONS
D50-08	8OZ	12	32 GL	Use 1 OZ to every 4 GL of fuel
D50-16	16 OZ	24	64 GL	Use 1 OZ to every 4 GL of fuel
D50-01	1 GL	6	512 GL	Use 1 GL to every 512 GL of fuel
D50-05	5 GL	1	2,560 GL	Use 1 GL to every 512 GL of fuel
D50-55	55 GL	1	28,160 GL	Use 1 GL to every 512 GL of fuel
D50-275	275 GL	1	140,800 GL	Use 1 GL to every 512 GL of fuel

An overtreatment of additive is not harmful.
For best results, add additive before filling tank.

Diesel Fire will not plug diesel particulate filters.

ULSD FORMULA

E-ZOIL performance additives are formulated for today's Ultra Low Sulfur Diesel. They meet all emission standards and provide added protection for your valuable diesel-powered equipment.

For warm weather diesel performance, reach for DIESEL FIRE!



E-ZOIL
Performance. Pour it on.

234 Fillmore Avenue, Tonawanda, New York 14150
855-MY-EZOIL EZOIL.com Made in the USA